

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

06/30/25

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Product name : SC Johnson Professional® Multi-Surface Floor Finish + Sealer

Recommended use : Floor Polish

Restrictions on use : Use only as directed on label

Manufacturer, importer, supplier : S.C. Johnson & Son, Inc.
1525 Howe Street
Racine WI 53403-2236

Telephone : +1-800-558-5252

Emergency telephone number : 24 Hour Medical Emergency Phone: (866)231-5406
24 Hour Transport Emergency Phone: (800)424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

This product does not meet the criteria for classification in any hazard class according to regulation OSHA 29 CFR 1910.1200.

Labelling

Precautionary statements

Other hazards : None identified

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Weight percent
Diethylene glycol monoethyl ether	111-90-0	5.00 - 10.00

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

Tributyoxethyl phosphate	78-51-3	1.00 - 5.00
Zinc oxide	1314-13-2	1.00 - 5.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact : No special requirements

Skin contact : No special requirements

Inhalation : No special requirements.

Ingestion : No special requirements

Most important symptoms and effects, both acute and delayed

Eyes : No adverse effects expected when used as directed.

Skin effect : No adverse effects expected when used as directed.

Inhalation : No adverse effects expected when used as directed.

Ingestion : No adverse effects expected when used as directed.

Indication of any immediate medical attention and special treatment needed

See Description of first aid measures unless otherwise stated.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards during firefighting : Container may melt and leak in heat of fire.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

Further information : Fight fire with normal precautions from a reasonable distance. Standard procedure for chemical fires. Wear full protective clothing and positive pressure self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wash thoroughly after handling.

Environmental precautions : Outside of normal use, avoid release to the environment.

Methods and materials for containment and cleaning up : Dike large spills.
Clean residue from spill site.

7. HANDLING AND STORAGE

Handling

Precautions for safe handling : Avoid contact with skin, eyes and clothing.
For personal protection see section 8.
KEEP OUT OF REACH OF CHILDREN AND PETS.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Storage

Requirements for storage areas and containers : Keep container closed when not in use.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer**

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Occupational Exposure Limits**

Components	CAS-No.	mg/m3	ppm	Non-standard units	Basis
Zinc oxide	1314-13-2	5 mg/m3	-	-	OSHA TWA
Zinc oxide	1314-13-2	5 mg/m3	-	-	OSHA TWA
Zinc oxide	1314-13-2	15 mg/m3	-	-	OSHA TWA
Zinc oxide	1314-13-2	10 mg/m3	-	-	ACGIH STEL
Zinc oxide	1314-13-2	2 mg/m3	-	-	ACGIH TWA

Personal protective equipment**Respiratory protection** : No special requirements.**Hand protection** : No special requirements.**Eye protection** : No special requirements.**Skin and body protection** : No special requirements.**Hygiene measures** : Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.**9. PHYSICAL AND CHEMICAL PROPERTIES****Form** : liquid**Color** : white**Odour** : Fruity Floral

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

Odour Threshold : Test not applicable for this product type

pH : 8.3
at (25 °C)

Melting point/freezing point : 0 C

Initial boiling point and boiling range : 100 C

Flash point : > 94 °C
> 201.2 °F

Evaporation rate : Test not applicable for this product type

Flammability (solid, gas) : The product is not flammable.

Upper/lower flammability or explosive limits : Test not applicable for this product type

Vapour pressure : Test not applicable for this product type

Vapour density : Test not applicable for this product type

Relative density : 1.03 g/cm³ at 25 °C

Solubility(ies) : dispersible

Partition coefficient: n-octanol/water : Test not applicable for this product type

Auto-ignition temperature : Test not applicable for this product type

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

Decomposition temperature	: Test not applicable for this product type	
Viscosity, dynamic	: 5.5 mPa.s	
Viscosity, kinematic	: Test not applicable for this product type	
Oxidizing properties	: Test not applicable for this product type	
Volatile Organic Compounds	: 0.1 % - additional exemptions may apply	
Total VOC (wt. %)*	*as defined by US Federal and State Consumer Product Regulations	
Other information	: None identified	:

10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: If accidental mixing occurs and toxic gas is formed, exit area immediately. Do not return until well ventilated.
Conditions to avoid	: Direct sources of heat.
Incompatible materials	: Do not mix with bleach or any other household cleaners. Strong bases
Incompatible materials	: Do not mix with bleach or any other household cleaners. Strong bases

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer**

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

Hazardous decomposition products : Thermal decomposition can lead to release of irritating gases and vapours.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : LD50 > 5000 mg/kg

Acute inhalation toxicity : LC50 > 10 mg/L

Acute dermal toxicity : LD50 > 5000 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas
Skin corrosion/irritation	No classification proposed	-
Eye irritation	No classification proposed	-
Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	No classification proposed	-
Specific target organ	No classification proposed	-

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer**

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

toxicity - repeated exposure		
Aspiration hazard	No classification proposed	-

Other information : see user defined free text**Aggravated Medical Condition** : None known.**12. ECOLOGICAL INFORMATION****Product** : The product itself has not been tested.**Toxicity**

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

Components	End point	Species	Value	Exposure time
Diethylene glycol monoethyl ether	flow-through test LC50	Ictalurus punctatus	6,010 mg/l	96 h
Tributyloxyethyl phosphate	semi-static test LC50 Measured	Oncorhynchus mykiss (rainbow trout)	24 mg/l	96 h
Zinc oxide				

Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Diethylene glycol monoethyl	static test	Daphnia magna (Water	1,982 mg/l	48 h

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer**

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

ether	EC50	flea)		
Tributyxyethyl phosphate	static test EC50 Measured	Daphnia magna (Water flea)	53 mg/l	48 h
Zinc oxide				

Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Diethylene glycol monoethyl ether	static test EC50 Read-across (Analogy)	Desmodesmus subspicatus (green algae)	> 100 mg/l	96 h
Tributyxyethyl phosphate	static test EC50	Pseudokirchneriella subcapitata (green algae)	61 mg/l	72 h
Zinc oxide				

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Diethylene glycol monoethyl ether	100 %	28 d	Readily biodegradable.
Tributyxyethyl phosphate	87 %	28 d	Readily biodegradable.
Zinc oxide	No data available		

Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n-Octanol/water (log)
-----------	-------------------------------	---

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer**

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

Diethylene glycol monoethyl ether	3,162	0.54
Tributyloxyethyl phosphate	5.8 Measured	3.75 Measured
Zinc oxide	No data available	

Mobility

Component	End point	Value
Diethylene glycol monoethyl ether	No data available	
Tributyloxyethyl phosphate	log Koc	2.5
Zinc oxide	No data available	

PBT and vPvB assessment

Component	Results
Diethylene glycol monoethyl ether	Not fulfilling PBT and vPvB criteria
Tributyloxyethyl phosphate	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.**13. DISPOSAL CONSIDERATIONS**

Consumer may discard empty container in trash, or recycle where facilities exist.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

Land transport

Not classified as dangerous in the meaning of transport regulations.

Sea transport

Not classified as dangerous in the meaning of transport regulations.

Air transport

Not classified as dangerous in the meaning of transport regulations.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

California Prop. 65 : This product is not subject to the reporting requirements under California's Proposition 65.

State Right To Know

Massachusetts RTK	Zinc oxide	1314-13-2
Minnesota HSL	Diethylene glycol monoethyl ether	111-90-0
	Zinc oxide	1314-13-2
New Jersey HRTK	Zinc oxide	1314-13-2
Pennsylvania RTKL	Water	7732-18-5
	Acrylic polymers	
	Diethylene glycol monoethyl ether	111-90-0
	Zinc oxide	1314-13-2
	Ammonium Hydroxide	1336-21-6
	Potassium hydroxide	1310-58-3
	2-ethoxyethanol	110-80-5
	Ethylene glycol	107-21-1
	Butan-1-ol	71-36-3

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer**

Version 1.0

Print Date 05/17/2023

Revision Date 03/10/2023

SDS Number 350000043505

GEN_SOF Number 77161

16. OTHER INFORMATION**HMIS Ratings**

Health	1
Flammability	0
Reactivity	0

NFPA Ratings

Health	1
Fire	0
Reactivity	0
Special	-

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment & Regulatory Affairs (GSARA)
-------------	--

Report for Website

Product Name:SCJ Pro MultiPurpose Floor Finish Bulk

Specification ID:350000043505

Ingredients	CAS Number	Function
Water	7732-18-5	Water
Proprietary Polymer	Proprietary	Polymer
Ethoxydiglycol	111-90-0	Solublizer
POLYACRYLATE-15	67892-91-5	Wax
Trimethyl Pentanyl Diisobutyrate	6846-50-0	Flow Agent
Ethanol, 2-butoxy-, 1,1',1''- phosphate	78-51-3	Flow Agent
Zinc Oxide	1314-13-2	Film Former
Hydrogen Peroxide	7722-84-1	Stabilizer
UNDECETH-5	34398-01-1	Wetting Agent
Caprylyl Pyrrolidone	2687-94-7	Surfactant
HEXYLOXYETHANOL	112-25-4	Solublizer
Phenoxyethanol	122-99-6	Solublizer
2-Propenoic acid, polymer with ethenylbenzene, butyl 2- propenoate and (1- methylethenyl)benzene	77045-85-3	Film Former
Pentasodium Pentetate	140-01-2	Chelator
Hexylene Glycol	107-41-5	Fragrances

READY-TO-USE MULTI-SURFACE FLOOR FINISH PLUS SEALER

FOR USE ON A VARIETY OF FLOORING HIGH PERFORMANCE FINISH / SEALER

SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer with FlexiFilm Technology™ is extremely tough, highly repairable and exhibits aggressive adhesion on most flooring substrates including VCT, Luxury Vinyl Tile (LVT), sheet vinyl, terrazzo, rubber, linoleum, honed marble or granite, and unglazed ceramic. With excellent resistance to scuffs, black heel marks, and dirt embedment, gloss level is quickly restored with multi-speed buffing. This is a versatile finish that is user-friendly - easy to apply and easy to strip, with a light fresh scent.

For best results use along with SC Johnson Professional® Heavy Duty Neutral pH Floor & Surface Cleaner Concentrate and SC Johnson Professional® Hyper Concentrate Floor Stripper.



**PROVIDES A CRYSTAL CLEAR FINISH. 40% WHITER THAN PREVIOUS
MULTI-SURFACE FLOOR FINISH + SEALER***

HIGH PERFORMANCE AND EFFICIENCY

- FlexiFilm Technology™ creates an extremely tough film that resists dirt, black heel marks and scuffs, and exhibits excellent buff response.

COST CONTROL

- Designed to deliver exceptional gloss and durability results while keeping maintenance frequencies and associated costs down.

VERSATILE

- Versatility in application methods from thin coating with a flat mop or applicator to thick coating with a string mop.
- Versatility in maintenance procedures from scrub & recoat to high speed burnishing.
- Versatility for use on most floor substrates.

SKU	DESCRIPTION	DILUTION RATES
362834	1 x 5 GAL (640 FL OZ) 18.97 L Bag In Box	Ready-To-Use
362822	4 x 1 GAL (128 FL OZ) 3.78 L	Ready-To-Use

*Using a modified ASTM D3210 testing method.



Use Instructions:
Place proper warning blockades around work area. **(Note: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.)**

Strip off old floor finish using **SC Johnson Professional® Hyper Concentrate Floor Stripper**, per label instructions.

APPLICATION: Apply 4-6 coats of finish using a clean mop or applicator. To achieve desired gloss level, apply additional coats according to label instructions. Allow 30-45 minutes dry time between coats. Temperature, humidity and air circulation affect drying time. Allow 24 hours cure time before maintenance.

MAINTENANCE: Dust mop or sweep area to be maintained. Clean floor with mop & bucket or automatic scrubbing machine. For best results use **SC Johnson Professional® Neutral pH Floor & Surface Cleaner** and **EZ Care Heavy Duty Scrubbing**

Pad following label instructions. **SC Johnson Professional® Multi-Surface Floor Finish Plus Sealer** is uniquely formulated to allow for dry buffing or UHS burnishing with a wide range of different pads and machines to achieve the desired appearance.

RE-COAT: Place proper warning blockades around work area. **(Note: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.)** Deep scrub the floor with mop & bucket or automatic scrubbing machine using **SC Johnson Professional® Neutral pH Floor & Surface Cleaner** and green or blue pad per label instructions for deep cleaning. Follow application instructions to apply additional finish to the floor.

REMOVAL: Strip off old floor finish using **SC Johnson Professional® Hyper Concentrate Floor Stripper** and black stripping pad, per label instructions.

SAFETY PRACTICES TO FOLLOW

It's good business practice to assure that your employees have read and understood the product labels and Safety Data Sheet before using this product. The label use directions and SDS contain important hazard warnings, precautionary statements and first aid procedures. This information is available on-line at www.scjp.com or by calling 800-248-7190. Wear personal protective equipment, chemical-resistant gloves and chemical splash goggles, when dispensing concentrates. Improper mixing or diluting of concentrate may damage surfaces and may result in physical harm to the user.

INGREDIENTS:
Water (7732-18-5); Acrylic Polymers (Proprietary); Ethoxydiglycol (111-90-0); POLYACRYLATE-15 (67892-91-5); Trimethyl Pentanyl Diisobutyrate (6846-50-0); Tributyoxyethyl Phosphate (78-51-3); Zinc Ammonium Carbonate (38714-47-5); Hexoxyethanol (112-25-4); Phenoxyethanol (122-99-6); 2-Propenoic acid, polymer with ethenylbenzene, butyl 2-propenoate and (1-methylethenyl)benzene, ammonium salt (360564-31-4); Fragrance (Proprietary); UNDECETH-5 (34398-01-1); Caprylyl Pyrrolidone (2687-94-7); Pentasodium Pentetate (140-01-2).

NOTE: Does not contain intentionally added PFAS* or Phthalates

*PFAS are perfluoroalkyl and polyfluoroalkyl substances, which are a class of fluorinated organic chemicals containing at least one fully fluorinated carbon atom.

PRODUCT SPECIFICATION

Description	Ready-To-Use
Color	White
pH at dilution	8.18
Density	1.0312 g/cm³
Fragrance	Light Fresh Scent
Shelf-Life	2 years
Incompatible materials	Do not mix with strong acids, bleach or any other cleaner. Strong bases.
Storage and Disposal	Keep from freezing. To avoid contamination, do not return unused product to original container. Dispose of container in accordance with all federal, state and local applicable regulations.